

TWINNY S

TWINNY S, 230V/2900W, combi-wedge short, gear 144:1, EU plug
Article 119.024



Article	119.024	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2900 W	
Temperature	20 – 600 °C	68.0 – 1112.0 °F
Air volume adjustable	Yes	
Speed	0.8 – 4.0 m/min	2.62 – 13.12 ft/min
Combi-wedge version	Short	
Hot wedge width	50 mm	1.96 in
Max. overlap	125 mm	4.92 in
Max. welding pressure	500 N	112.4 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Brushless blower motor	No	
LQS	No	
Length	350.0 mm	13.77 in
Width	390.0 mm	15.35 in
Height	270.0 mm	10.62 in
Weight	6.9 kg	15.21 lb
Welding materials	HD-PE	
	LD-PE	
	LLD-PE	
	PVC	
	PP	
	TPO	



TWINNY S

TWINNY S, 230V/2900W, combi-wedge
short, gear 144:1, EU plug
Article 119.024

	FPO	
	CSPE	
	EPDM	
Plug	EU, 3 poles, 16A	
Power cable length	3.0 m	9.84 ft
Conformity mark	CE	
Protection class	II	